http://algs4.cs.princeton.edu

2.1 H-SORTING DEMO

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.



h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.

h-sorting demo

In iteration `i`, swap `a[i]` with each larger entry `h` positions to its left.

h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.



h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.



h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.



h-sorting demo

An array is `h`-sorted if `a[i-h] <= a[i]` for each `i`.